



## DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Product Regulation)

DoP \_ [EN] \_ 002 \_ Nr. Z-495195

1. Unique identification code of product-type:  
**ZETTEX MS60**
  
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**Batch number: See product packaging**
  
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Sealants for façade elements**  
**Sealants for sanitary joints**  
**Sealants for pedestrian walkways**  
**EN 15651-1: F-EXT-INT-CC (CLASS 25HM)**  
**EN 15651-3: S (CLASS XS3)**  
**EN 15651-4: PW-EXT-INT-CC (CLASS 25HM)**
  
4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):  
**ZETTEX EUROPE B.V. ■ PLAZA 20 ■ NL - 4782 RW MOERDIJK**
  
5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant
  
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3**  
**System 3 for reaction to fire**
  
7. In case of declaration of performance concerning a construction product covered by a harmonized standard:  
**The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-3 / EN 15651-4 and reaction to fire under system 3 and issued a test report.**
  
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant



**9. Declared performance**

Conditioning: Procedure B (according to ISO 8340)  
 Substrate: Mortar M1 (with primer P03)  
 Glass (without primer)  
 Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

Substrate: Glass (without primer)  
 Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 20 %	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	3	
Durability	Pass	



**Substrate: Mortar M1 (with primer P03)**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-4:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Tensile properties at maintained extension	NF	
Loss of volume	≤ 10 %	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus: ≤ 50 %	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

(\*) See material safety data sheet  
 NPD: No Performance Determined  
 NF: No Failure  
 NR: Not required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Zettex Europe B.V.  
 Plaza 20 • 4782 RW • Moerdijk  
 T +31 (0)888-93 88 39 • F +31(0)888-93 88 88  
 I www.zettex.com • E sales@zettex.com